

Technical Data		Audi Q4 45 e-tron quattro 195 kW	
Program for Germany		Status: 09/14/21	
Drivetrain / Battery			
Peak electrical output in kW (PS)		195 (265)	
Continuous electrical output in kW		77	
Electrical torque output in Nm (<i>lb-ft</i>)		425 (313.5 <i>lb-ft</i>)	
Battery type		Lithium-ion	
Battery capacity gross / net in kWh		82 / 76.6	
Max. charging capacity AC / DC in kW		11.0 / 125	
Charging time DC 5-80% in min		38	
Charging time AC 0-100%, 3ph 16A@230V in min		450	
12V battery in A / Ah		280 / 51	
On-board voltage 1 in volts		12	
On-board voltage 2 in volts		400	
Drivetrain / transmission			
Drive type		All-wheel drive	
Transmission type		1-speed / automatic	
Suspension / steering / brakes			
Type and design of front-axle suspension		MacPherson struts, front	
Type and design of rear-axle suspension		4-link rear axle	
Steering		Electromechanical steering with speed-dependent power assistance	
Steering ratio		15.6	
Turning circle in m (<i>ft</i>)		11.5 (37.7 <i>ft</i>)	
Brake control system		Dual-circuit brake system with diagonal split, ESC/ABS/EBD, brake booster, hydraulic brake assist	
Tires (basic) front rear		235/55 R19 255/50 R19	
Wheels (basic) front rear		Steel 8 J x 19" 8 J x 19"	
Performance / acoustics			
Top speed in km/h (<i>mph</i>)		180 (111.8 <i>mph</i>)	
Limited		yes	
Electrical acceleration, 0-100 km/h (62.1 <i>mph</i>) in s		6.9	
Exterior noise level when stationary / drive-past as per ECE R51.03 in dB (A)		- / 66	
Consumption / range			
Electric power consumption, combined, in kWh/100 km (62.1 <i>mi</i>)*		21.3 – 17.9 (WLTP) 18.2 – 16.5 (NEDC)	
CO ₂ emissions, combined, in g/km (<i>g/mi</i>)		0	
Electrical range, combined according to WLTP in km (<i>mi</i>)*		490 - 412 (304.5 - 256.0 <i>mi</i>)	
Servicing / guarantee (Germany)			
Service interval		2 years	
Vehicle / paint / rust perforation guarantee		2 / 3 / 12 (years)	
Insurance classification in Germany: third party / fully comprehensive / part-comprehensive		16 / 22 / 22	
Weights / loads			
Unladen weight without driver / with driver / gross weight limit in kg (<i>lb</i>)		2135 / 2210 / 2720 (4706.9 / 4872.2 / 5996.6 <i>lb</i>)	
Front/rear axle load limit in kg (<i>lb</i>)		1270 / 1515 (2799.9 / 3340.0 <i>lb</i>)	
Trailer load limit on 8% / 12% gradient, braked // unbraked in kg (<i>lb</i>)		1200 / 1200 // 750 (2645.5 / 2645.5 / 1653.5 <i>lb</i>)	
Roof load limit / permissible nose weight in kg (<i>lb</i>)		75 / 75 (165.3 / 165.3 <i>lb</i>)	

Capacities	
Cooling system capacity (incl. heating) in l (<i>US gal</i>)	11.5 (3.0 <i>US gal</i>)
Dimensions / body	
Body type / number of doors	Unitary steel / 5
Number of seats	5
Drag coefficient C_d / frontal area A in m ² (<i>sq ft</i>)	0.28 / 2.56 (3.0 / 27.6 <i>sq ft</i>)
Standard dimensions (length / width excluding mirrors / height with steel springs / height with air springs) in mm (<i>ft</i>)	4588 / 1865 / 1632 / - (15.1 / 6.1 / 5.4 <i>ft</i>)
Width including mirrors in mm (<i>ft</i>)	2108 (6.9 <i>ft</i>)
Wheelbase / track width front/rear in mm (<i>ft</i>)	2764 / 1587 / 1565 (9.1 / 5.2 / 5.1 <i>ft</i>)
Overhang angle of steel springs, front/rear in degrees	16.90 / 19.40
Height of loading edge with steel springs / air springs in mm (<i>ft</i>)	783 / - (2.6 <i>ft</i>)
Open luggage compartment - behind the 2nd seat row in l (<i>cu ft</i>)	520 (18.4 <i>cu ft</i>)
Largest luggage capacity - behind the 1st seat row in l (<i>cu ft</i>)	1490 (52.6 <i>cu ft</i>)

* Figures depend on the equipment selected.