

Technical Data		Audi Q4 Sportback 50 e-tron quattro 220 kW	
Program for Germany		Status: 09/14/21	
Drivetrain / battery			
Peak electrical output in kW (PS)		220 (299)	
Continuous electrical output in kW		77	
Electrical torque output in Nm (<i>lb-ft</i>)		460 (339.3)	
Battery type		Lithium-ion	
Battery capacity gross / net in kWh		82 / 76.6	
Max. charging capacity AC / DC in kW		11.0 / 125	
Charging time DC 5-80% in min		38	
Charging time AC 0-100%, 3ph 16A@230V in min		450	
12V battery in A / Ah		280 / 51	
On-board voltage 1 in volts		12	
On-board voltage 3 in volts		400	
Drivetrain / transmission			
Drive type		All-wheel drive	
Transmission type		1-speed / automatic	
Suspension / steering / brakes			
Type and design of front-axle suspension		MacPherson struts, front	
Type and design of rear-axle suspension		4-link rear axle	
Steering		Electromechanical steering with speed-dependent power assistance	
Steering ratio		15.6	
Turning circle in m (<i>ft</i>)		11.5 (37.7)	
Brake control system		Dual-circuit brake system with diagonal split, ESC/ABS/EBD, brake booster, hydraulic brake assist	
Tires (basic) front rear		235/55 R 19 255/50 R 19	
Wheels (basic) front rear		Steel 8 J x 19" 8 J x 19"	
Performance / acoustics			
Top speed in km/h (<i>mph</i>)		180 (111.8)	
Limited		yes	
Electrical acceleration, 0-100 km/h (62.1 <i>mph</i>) in s		6.2	
Exterior noise level when stationary / drive-past as per ECE R51.03 in dB (A)		- / 66	
Consumption / range			
Electric power consumption, combined, in kWh/100 km (62.1 <i>mi</i>)*		20.9 - 17.5 (WLTP) 17.9 - 16.4 (NEDC)	
CO ₂ emissions, combined, in g/km (<i>g/mi</i>)		0	
Electrical range, combined according to WLTP in km (<i>mi</i>)*		497 - 420 (308.8 - 261.0)	
Servicing / guarantee (Germany)			
Service interval		2 years	
Vehicle / paint / rust perforation guarantee		2 / 3 / 12 (years)	
Insurance classification in Germany: third party / fully comprehensive / part-comprehensive		16 / 24 / 22	
Weights / loads			
Unladen weight without driver / with driver / gross weight limit in kg (<i>lb</i>)		2140 (4717.9) / 2215 (4883.2) / 2715 (5985.6)	
Front/rear axle load limit in kg (<i>lb</i>)		1275 (2810.9) / 1510 (3329.0)	
Trailer load limit on 8% / 12% gradient, braked // unbraked in kg (<i>lb</i>)		1200 (2645.5) / 1200 (2645.5) // 750 (1653.5)	
Roof load limit / permissible nose weight in kg (<i>lb</i>)		75 (165.3) / 75 (165.3)	

Capacities	
Cooling system capacity (incl. heating) in l (<i>US gal</i>)	11.5 (3.0)
Dimensions / body	
Body type / number of doors	Unitary steel / 5
Number of seats	5
Drag coefficient C_d / frontal area A in m ² (<i>sq ft</i>)	0.27 / 2.56 (27.6)
Standard dimensions (length / width excluding mirrors / height with steel springs / height with air springs) in mm (<i>ft</i>)	4588 (15.1) / 1865 (6.1) / 1614 (5.3) / -
Width including mirrors in mm (<i>ft</i>)	2108 (6.9)
Wheelbase / track width front/rear in mm (<i>ft</i>)	2764 (9.1) / 1587 (5.2) / 1565 (5.1)
Overhang angle of steel springs, front/rear in degrees	16.90 / 19.40
Height of loading edge with steel springs / air springs in mm (<i>ft</i>)	783 (2.6) / -
Open luggage compartment - behind the 2nd seat row in l (<i>cu ft</i>)	535 (18.9)
Largest luggage capacity - behind the 1st seat row in l (<i>cu ft</i>)	1460 (51.6)

* Figures depend on the equipment selected.